

## Quartz Design Self Adhesive PVC Film For Kitchen Countertop Renewed

### Our Product Introduction

for more products please visit us on [realsundeco.com](http://realsundeco.com)

#### Basic Information

- Place of Origin: Foshan, China
- Brand Name: Realsun Deco
- Minimum Order Quantity: 3000m/model
- Price: Negotiable
- Packaging Details: Pack in roll
- Delivery Time: 15-20 days
- Payment Terms: T/T 30% down payment, 70% balance before shipment
- Supply Ability: 500000m/month



#### Product Specification

- Design: Wood Grain, Marble, Brick, Stone, Plain Color Etc.
- Adhesive Strength: High
- Size: 122cm\*50m, 60cm\*10m
- Adhesive: Acrylic Pressure Sensitive Adhesive
- Thickness: 0.08mm-0.15mm
- Waterproof: Yes
- Liner Paper: 80gsm, 100gsm, 120gsm
- Durability: Excellent
- Highlight: **Countertop Renewed Self Adhesive PVC Film,**  
**Countertop Renewed self adhesive furniture film**

## Product Description

### Product Description:

Our self adhesive pvc film is a durable and versatile synthetic plastic material composed of polyvinyl chloride. A layer of pressure sensitive adhesive is applied to the back for secure attachment to a variety of surfaces. Our self adhesive pvc film comes in a range of thicknesses to suit any application from wall covering to craft and DIY projects. It is available in a range of finishes like glossy, matte, satin and textured. Customers can also pick from a range of colors and patterns such as wood grain and marble that give the material added aesthetic appeal.

Our self adhesive pvc film can be conveniently used to cover walls and furniture. The self adhesive properties make for an easy application for both professional and amateur users. It is also popular for use in craft and DIY projects.

### Features:

Product Name: Self Adhesive PVC Film

Design: Wood Grain, Marble, Brick, Stone, Plain Color Etc.

Adhesive: Acrylic Pressure Sensitive Adhesive

Size: 122cm\*50m, 60cm\*10m

Material: PVC

Thickness: 0.08mm-0.15mm

Contact Paper Rolls

Contact Paper

Self Adhesive Vinyl Rolls

### Technical Parameters:

We provide various kinds of wallpapers with different sizes and designs. The thickness ranges from 0.1mm to 0.12mm, and our wallpaper comes in two widths options, 1220mm and 600mm. Lengthwise, these products come in 50m/roll and 10m/roll options. As for color patterns, we provide Wood grain, Solid color, Marble, Brick and other designs. In terms of surface treatment, we provide Matt, Super matt, embossed, high gloss and soft touch. We also appreciate OEM and ODM orders.

### Applications:

Self-adhesive PVC film is a versatile material that can be used for various applications, including home improvement, crafts, signage, and more. Here's a general guide on how to apply self-adhesive PVC film:

Materials you'll need:

Self-adhesive PVC film

A clean, smooth surface to apply the film to (e.g., furniture, walls, windows, or any other suitable surface)

A measuring tape or ruler

A sharp utility knife or scissors

A squeegee or a credit card

A clean cloth or sponge

A spray bottle with soapy water (optional)

Steps for application:

Prepare the surface: Ensure that the surface you plan to cover with self-adhesive PVC film is clean, dry, and smooth. Remove any dust, dirt, or imperfections. If the surface is dirty, clean it thoroughly and let it dry completely.

Measure and cut: Measure the dimensions of the surface you want to cover and add a few extra inches to each side to allow for trimming. Cut the self-adhesive PVC film to the desired size using a sharp utility knife or scissors. Be precise in your measurements and cutting to ensure a proper fit.

Peel off the backing: Carefully peel back a few inches of the backing paper from one end of the PVC film. Avoid touching the adhesive side to prevent fingerprints and dirt from sticking to it.

Apply the film: Begin applying the exposed adhesive side of the PVC film to the surface. Start at one corner or edge and align it with the surface. As you apply the film, gradually peel off more of the backing paper, smoothing the film onto the surface as you go. You can use a squeegee or a credit card to help remove any air bubbles and ensure a smooth, even application.

Smooth out bubbles: If you notice any air bubbles trapped under the film, use the squeegee or credit card to gently push them out towards the edges. Work from the center outward to expel the bubbles completely.

Trim excess: Once the film is applied smoothly, use a utility knife or scissors to trim any excess film along the edges. Be cautious when cutting to avoid damaging the surface underneath.

Finish and clean: After trimming, go over the entire surface with a clean cloth or sponge to ensure that the PVC film is securely adhered and free from any air bubbles or wrinkles. If you used soapy water during application, wipe away any excess water or soap residue.

Final inspection: Inspect the surface to ensure that the PVC film is securely in place and free from imperfections. If you encounter any issues, gently lift the film and reapply as needed.

Self-adhesive PVC film can be used for a wide range of purposes, so make sure to follow the specific instructions provided by the manufacturer if you have a unique application in mind. Proper surface preparation and careful installation are key to achieving a professional-looking result.

## Customization:

Self Adhesive PVC Film

Realsun Deco provides custom self adhesive PVC film services with the following features:

Brand Name: Realsun Deco

Place of Origin: Foshan, China

Minimum Order Quantity: 3000m/model

Price: Negotiable

Packaging Details: Pack in roll

Delivery Time: 15-20 days

Payment Terms: T/T 30% down payment, 70% balance before shipment

Supply Ability: 500000m/month

Waterproof: Yes

Design: Wood Grain, Marble, Brick, Stone, Plain Color Etc.

Adhesive: Acrylic Pressure Sensitive Adhesive

Thickness: 0.08mm-0.15mm

Size: 122cm\*50m, 60cm\*10m

Ideal for self adhesive plastic film, adhesive contact paper, contact paper and more.

## Packing and Shipping:

For the packaging and shipping of Self Adhesive PVC Film, the following should be taken into consideration:

The film should be properly packaged and sealed to ensure that no dirt or moisture is trapped in.

The film should be stored in a dry and cool area, away from heat and direct sunlight.

The film should be shipped in a box or envelope and must be properly labeled.

The film should be shipped with appropriate padding and cushioning to prevent it from being damaged during transit.



**Foshan Realsun Decorative Material Co., Ltd.**



+8613790066054



sale1@realsundeco.com



realsundeco.com

Room 706, Build 1, No 121 North of Lingnan Avenue, Foshan, China